



# SciCron Technologies, LLC

## SAFETY DATA SHEET

### 1. IDENTIFICATION

**PRODUCT NAME:** TMF-300™ Check Film

**SDS NUMBER:** SC-001-SDS

**GENERIC NAME:** Static Dissipative Film

**DATE ISSUED:** June 5, 2018

**MANUFACTURER:** SciCron Technologies, LLC

**MANUFACTURER PHONE:** 806-372-8300

**ADDRESS:** 501 Amarillo Blvd. West

**MANUFACTURER FAX:** 806-372-8333

**CITY, STATE, ZIP:** Amarillo, TX 79107

**EMERGENCY (PLANT MANAGER):** 806-372-8300

### 2. HAZARDS IDENTIFICATION

This material is classified as not hazardous under OSHA regulations. Under normal conditions of use, this product is not expected to create any unusual industrial hazards. Irritating gases/fumes may be given off during burning or thermal decomposition. Contact with hot material with cause thermal burns.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization: > 99% Polyethylene Terephthalate (PET) [CAS # 25038-59-9]  
<1.0% Coating [Proprietary]

### 4. FIRST AID MEASURES

**Most Important Symptom(s)/Effect(s)**

**INHALATION:** Move to fresh air.

**EYE CONTACT:** Flush with large amounts of water until irritation subsides. Obtain medical attention.

**SKIN CONTACT:** If molten material contacts skin, cool rapidly with cold water and obtain medical attention for thermal burn.

**INGESTION:** This material is not expected to be absorbed within the gastrointestinal tract, therefore induction of vomiting should not be necessary

### 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Carbon dioxide, dry chemical, or water.

**Fire Fighting Procedure:** Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritating fumes.

**Fire/Explosion Hazards:** This product is a combustible thermoplastic material that burns vigorously with intense heat.

## 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTION:** Ensure adequate ventilation. Wear personal protective equipment. Do not breathe dust. Remove all sources of ignition.

**ENVIRONMENTAL PRECAUTIONS:** Do not allow to enter soil, waterbodies, or drains.

**METHODS FOR CLEANING UP:** Avoid generation of dust. Remove all sources of ignition. Sweep or scoop up into closed containers for disposal.

## 7. HANDLING AND STORAGE

**MAX:** Storage Temperature: 90°F / 32°C

**HANDLING:** Ensure appropriate exhaust and ventilation at machinery and at places where dust can be generated. Avoid dust formation, accumulation of static charges. Prohibit sources of spark and ignition, such as smoking. Processing of this product under high temperatures will cause hazardous emissions of vapors, carbon monoxide, or carbon dioxide.

**STORAGE:** If this material is stored under ambient temperature conditions, it is not hazardous. However, extensive storing at higher than 581°F / 305°C will emit vapors, carbon monoxide, or carbon dioxide.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**EXPOSURE GUIDELINES:** Not applicable

**VENTILATION MEASURES:** Provide good ventilation and/or an exhaust system in the work area.

**EYE PROTECTION:** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations 29 CFR 1910.133 or European standard EN166

**RESPIRATORY PROTECTION:** None required under normal conditions.

**SKIN AND BODY PROTECTION:** Wear appropriate protective gloves and clothing to prevent skin exposure.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL FORM:** Solid Sheet  
**APPEARANCE:** Clear to Opaque  
**ODOR:** Not Applicable  
**pH:** Not Applicable  
**MELTING POINT:** 482°F / 250°C  
**BOILING POINT:** Not Available  
**FLASH POINT:** Not Determined  
**DECOMPOSITION TEMPERATURE:** 581°F / 305°C  
**AUTO-IGNITION TEMPERATURE:** 734°F (390°C) approx.  
**EXPLOSION LIMITS:** Not Applicable  
**EVAPORATION RATE:** Not Applicable  
**VAPOR PRESSURE:** Not Applicable  
**VAPOR DENSITY:** Not Applicable  
**RELATIVE DENSITY:** 1.1 approx.  
**SOLUBILITY IN WATER:** Insoluble

## 10. STABILITY AND REACTIVITY

**STABILITY:** Product is stable under normal conditions.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**INCOMPATIBILITIES:** Strong oxidizing agents, strong acids, & strong bases.

**DECOMPOSITION PRODUCTS:** Carbon Monoxide & Carbon Dioxide from burning. When heated to decomposition, vapors can react with oxidizing materials forming strong acrid fumes.

**CONDITIONS TO AVOID:** Incompatible products. Excess heat. Keep away from open flames, hot surfaces, and ignition sources.

## 11. TOXICOLOGICAL INFORMATION

No known toxicities.

## 12. ECOLOGICAL INFORMATION

**ECOTOXICITY:** This product is a solid, inert product with low volatility and is essentially insoluble in water.

**MOBILITY:** Due to the solid nature of this product, it should have low mobility in soil.

**PERSISTANCE & DEGRADABILITY:** This product is non-biodegradable.

**BIOACCUMULATION:** This solid product has a low potential for bioaccumulation.

## 13. DISPOSAL CONSIDERATIONS

Waste disposal should be in accordance with all federal, state, and local environmental laws and regulations.

## 14. TRANSPORTATION INFORMATION

Not subject to national and international regulations on the transport of dangerous goods.

## 15. REGULATORY INFORMATION

<b>OSHA HAZARD COMMUNICATION:</b>	Non- Hazardous
<b>TOXIC SUBSTANCES CONTROL ACT:</b>	Components listed
<b>CERCLA HAZARDOUS SUBSTANCES (40CFR302):</b>	None
<b>SARA SECTION 311/312:</b>	
Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of pressure hazard	No
Reactive Hazzard	No

## 16. OTHER INFORMATION

HMIS Rating: Health = 0 Flammability = 1 Reactivity Hazard = 0

AS OF THE DATE OF THIS DOCUMENT, THE FOREGOING INFORMATION IS BELIEVED TO BE ACCURATE AND IS PROVIDED IN GOOD FAITH TO COMPLY WITH APPLICABLE FEDERAL AND STATE LAWS. HOWEVER, NO WARRANTY OR REPRESENTATION OF LAW OR FACT, WITH RESPECT TO SUCH INFORMATION, IS INTENDED OR GIVEN.